

### Gunmetal CE Angled Type Safety Valve



642

For the protection of pressure vessels/systems for neutral/non-neutral vapours, gases, liquids, steam  
Screwed BSPP Female, ISO 4126-1, PED, CE and WRAS approved, -50°C to +200°C (PTFE Seals)



Gunmetal Bronze Body

Inlet	Outlet	Orifice	L	Range
1/2	1/2	15mm	35	0.5 - 16 BAR
3/4	3/4	20mm	42	
1	1	25mm	45	
1.1/4	1.1/4	32mm	47	
1.1/2	1.1/2	40mm	58	
2	2	50mm	58	
2.1/2	2.1/2	65mm	80	

Valves are supplied to your specific application and performance requirements

Valves are set and sealed at the factory

Call us on 01424 444222 for a tailored quotation

### Gunmetal CE Angled Type Safety Valve



652

For the protection of pressure vessels/systems for neutral/non-neutral vapours, gases, liquids and steam.  
Screwed BSPP Female, ISO 4126-1, TUV, PED, CE, -60°C to +130°C (NBR Seals)



Gunmetal Bronze Body

Inlet	Outlet	Orifice	L	Range
1/2	1/2	15mm	26	1 - 16 BAR
3/4	3/4	20mm	31	
1	1	25mm	35	
1.1/4	1.1/4	32mm	40	
1.1/2	1.1/2	40mm	46	
2	2	50mm	54	

Valves are supplied to your specific application and performance requirements

Valves are set and sealed at the factory

Call us on 01424 444222 for a tailored quotation

### Gunmetal CE Angled Type Safety Valve



851

For the protection of pressure vessels/systems for neutral/non-neutral vapours, gases, liquids and steam.  
Screwed BSPP Female, ISO 4126-1, TUV, PED, CE, -60°C to +220°C (PTFE Seals)



Gunmetal Bronze Body

Inlet	Outlet	Orifice	L	Range
1/2	1	15mm	40	0.5 - 50 BAR
3/4	1.1/4	20mm	43	
1	1.1/2	25mm	50	
1.1/4	2	32mm	61	
1.1/2	2	32mm	61	
2	2	32mm	61	

Valves are supplied to your specific application and performance requirements

Valves are set and sealed at the factory

Call us on 01424 444222 for a tailored quotation

### Brass CE Atmospheric Discharge Safety Valve

For the protection of pressure tanks/systems for air and other neutral gases.  
Screwed BSPP Male, ISO 4126-1, PED and CE approved, -20°C to +200°C (FKM Seats)



Brass Body

Inlet	Orifice	Range
1/4	8mm	0.2 - 50 BAR
3/8	10mm	
1/2	15mm	
3/4	20mm	
1	25mm	

Valves are supplied to your specific application and performance requirements

Valves are set and sealed at the factory

Call us on 01424 444222 for a tailored quotation



810

### Brass CE Atmospheric Discharge Safety Valve

For the protection of pressure tanks/systems for air and other neutral gases.  
Screwed BSPP Male, ISO 4126-1, PED and CE approved, -30°C to +130°C (NBR Seats)



Brass Body with Twist Type Lifting Mechanism

Inlet	Orifice	Range
1/2	15mm	0.2 - 50 BAR
3/4	20mm	
1	25mm	
1.1/4	32mm	
1.1/2	40mm	
2	50mm	

Valves are supplied to your specific application and performance requirements

Valves are set and sealed at the factory

Call us on 01424 444222 for a tailored quotation



812

### Brass CE Atmospheric Discharge Safety Valve with Shroud

For the protection of pressure tanks/systems for air and other neutral gases.  
Specifically designed for dirty environments, liquid, granular and dusty media  
Screwed BSPP Male, ISO 4126-1, PED and CE approved, -20°C to +200°C (FKM Seats)



Brass Body with Twist Type Lifting Mechanism

Inlet	Orifice	Range
1/2	15mm	0.2 - 6 BAR
3/4	20mm	
1	25mm	
1.1/4	32mm	
1.1/2	40mm	
2	50mm	

Valves are supplied to your specific application and performance requirements

Valves are set and sealed at the factory

Call us on 01424 444222 for a tailored quotation



813

### Gunmetal Pressure Relief Valve



For the protection of pressure vessels/systems for neutral/non-neutral vapours, gases, liquids and steam.  
Screwed BSPP Female. PED Approved. -60°C to +225°C (PTFE Seals)



Gunmetal Bronze Body

Inlet	Outlet	Orifice	Range
3/8	3/8	10mm	
1/2	1/2	15mm	
3/4	3/4	20mm	0.2 - 0.8 BAR
1	1	25mm	0.5 - 2.5 BAR
1.1/4	1.1/4	32mm	2 - 12 BAR
1.1/2	1.1/2	40mm	12 - 20 BAR
2	2	50mm	

Valves are supplied to your specific application and performance requirements

Valves can be supplied set or unset within a spring range

Call us on 01424 444222 for a tailored quotation

618

### Pressure Reducing Valve



Brass Body, Outlet 0.5 to 6 BAR, Max Inlet 25 BAR, 1/4 Gauge Port  
Screwed BSP Female, -10°C to +80°C



Without Gauge

Size	1/2	3/4	1	1.1/4	1.1/2	2
L	75	85	89	125	130	138

PRV

### Gunmetal Pressure Reducing Valve



For the protection of domestic and commercial water supply systems and industrial plants.  
Screwed Ends Union BSPT Male, DVGW, ACS, PED, CE, WRAS approved. -10°C to +95°C (EPDM Seals)



Gunmetal Body

Inlet	Outlet	Orifice	Inlet	Outlet
1/2	1/2	15mm		
3/4	3/4	20mm		
1	1	25mm	25 BAR	0.5 - 2 BAR
1.1/4	1.1/4	32mm	40 BAR	1 - 8 BAR
1.1/2	1.1/2	40mm	40 BAR	5 - 15 BAR
2	2	50mm		

Valves are supplied to your specific application and performance requirements

Valves can be supplied set or unset within a spring range

Call us on 01424 444222 for a tailored quotation

681

### Gunmetal Flanged Pressure Reducing Valve



For the protection of domestic and commercial water supply systems and industrial plants.  
Flanged Ends PN16, DVGW, ACS, PED, CE, WRAS approved. -10°C to +95°C (EPDM Seals)



Gunmetal Bronze Body

Inlet	Outlet	Orifice	Inlet	Outlet
DN25	DN25	25mm		
DN32	DN32	32mm		
DN40	DN40	40mm	25 BAR	0.5 - 2 BAR
DN50	DN50	50mm	40 BAR	1 - 8 BAR
DN65	DN65	65mm	40 BAR	5 - 15 BAR
DN80	DN80	80mm		
DN100	DN100	100mm		

Valves are supplied to your specific application and performance requirements

Valves can be supplied set or unset within a spring range

Call us on 01424 444222 for a tailored quotation

682